

vagrantfile

- provisioning: <https://www.vagrantup.com/docs/provisioning>

Vagrant.configure("2") do |config|

- config namespace: https://www.vagrantup.com/docs/vagrantfile/machine_settings#machine-settings

box

- box a usar: **config.vm.box**
 - config.vm.box=«debian/bullseye64»
- versión de la box a usar: **config.vm.box_version**
 - config.vm.box_version=«11.20211230.1»
- dirección URL de la box: **config.vm.box_url**
 - config.vm.box_url=«<https://app.vagrantup.com/debian/boxes/bullseye64>»

hostname

provision

- **name**: nombre del provisionar (para info)
- **type**:
 - shell
 - file
- **after**: (experimental)
 - https://www.vagrantup.com/docs/provisioning/basic_usage#dependency-provisioners
 - all
 - each
- **before**: (experimental)
 - https://www.vagrantup.com/docs/provisioning/basic_usage#dependency-provisioners
 - all
 - each
- communicator_required
- run
 - always
 - never
 - once
- inline (key/value):

```
config.vm.provision [name] type: "shell", path: "bootstrap.sh"
```

- Ruby block:

```
config.vm.provision [name] :shell, inline: "echo hello"
```

- ```
config.vm.provision [name] "shell" do |s|
 s.inline = "echo hello"
```

```
end
```

- `config.vm.provision [name] :file, path: "bootstrap.sh"`

**network**

**sync\_folder**

**provider**

**define**

From:  
<https://matebcn.eu/> - miguel angel torres egea

Permanent link:  
<https://matebcn.eu/tech:vagrant:vagrantfile>

Last update: **14/02/2022 19:45**

